

Four-way Cassette



Four-way Cassette

Features

- Auto Defrosting
- Auto Restart Function
- Anti-Cold Air Function
- LED Display
- Sleep Mode
- Independent Dehumidification
- Slim Design
- Wide-angle Air flow
- Quiet Design
- Timer
- Fresh Air
- Built-in Drain Pump

Specification_Four-way Cassette

Indoor Unit		MCC-24HR-Q	MCC-36HR-Q	MCC-36HR-R	MCC-48HR	MCC-60HR
Outdoor Unit		MOU-24H-Q	MOU-36H-Q	MOU-36H-R	MOU-48H	MOU-60H
Cooling Capacity	Btu/h	24000	36000	36000	48000	60000
	kW	7.0	10.5	10.5	14.0	17.6
Heating Capacity	Btu/h	26000	40000	38000	51000	60000
	kW	7.6	11.7	11.1	14.9	17.6
Power Supply	V~, Hz, Ph	220-240, 50, 1	220-240, 50, 1	380-415, 50, 3	380-415, 50, 3	380-415, 50, 3
Power Input (kW)	Cooling	2518	3950	4100	5054	6710
	Heating	2413	3985	3600	5241	5960
EER	W/W	2.82	2.67	2.57	2.77	2.62
COP	W/W	3.15	2.94	3.09	2.85	2.95
Air Flow Volume	m ³ /h	1220/1010/820	1648/1501/1326	1648/1501/1326	1650/1412/1264	1830/1480/1120
Noise Level (dB(A))	Hi/Med/Low	47/40/35	50/45/43	50/45/43	50/46/42	50/45/44
Net Dimension (mm)	Body (W×H×D)	840x230x840	840x300x840	840x300x840	840x300x840	840x300x840
	Panel (W×H×D)	950x55x950	950x55x950	950x55x950	950x55x950	950x55x950
Net Weight (kg)	Body	24	28.5	30	29	32
	Panel	5	5	5	5	5
Packing Dimension (mm)	Body (W×H×D)	900x250x900	900x320x900	900x320x900	900x320x900	900x320x900
	Panel (W×H×D)	1035x90x1035	1035x90x1035	1035x90x1035	1035x90x1035	1035x90x1035
Gross Weight (kg)	Body	30	30	36	33	38
	Panel	8	8	8	8	8
Piping Size (mm)	Liquid	Φ9.52(3/8")	Φ9.52(3/8")	Φ9.52(3/8")	Φ9.52(3/8")	Φ9.52(3/8")
	Gas	Φ15.9(5/8")	Φ19(3/4")	Φ19(3/4")	Φ19(3/4")	Φ19(3/4")
	Drainage	ODΦ32	ODΦ32	ODΦ32	ODΦ32	ODΦ32
Refrigerant		R22	R22	R22	R22	R22

1.The above design and specifications are subject to change of product improvement without prior notice .
2.The noise level data reflects the level in anechoic chamber .

Dealer Details: