

R Split

Features



Specifications_R Series

Model No.		CSA-09HR	CSA-12HR	CSA-18HR	CSA-24HR	CSA-30HR
Cooling Capacity	Btu/h	9000	12000	18000	24000	30000
	kW	2.6	3.5	5.3	7.0	8.8
Heating Capacity	Btu/h	9500	12000	18000	24000	30000
	kW	2.8	3.5	5.4	6.7	8.8
Power Supply	V~,Hz,Ph	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1
Power Input (W)	Cooling	1010	1350	2060	2700	3370
	Heating	920	1310	1595	2340	3140
Operating Current (A)	Cooling	4.6	6.1	9.5	12.0	15.0
	Heating	4.2	5.8	7.4	10.5	14.0
Starting Current	A	18.2	29.6	43.1	54.0	63.4
EER	W/W	2.61	2.61	2.56	2.61	2.61
COP	W/W	3.03	2.63	3.31	3.01	2.81
Air Flow Volume (m3/h)	Indoor	500/400/350	540/490/380	760/690/620	980/940/790	1050/1000/900
	Indoor(Hi/Med/Lo)	38/33/30	42/39/36	45/43/36	45/40/37	50/45/42
Noise Level (dB(A))	Outdoor	53	55	56	61	62
	Indoor (W*H*D)	710x250x189	790x275x196	930x275x198	1036x315x230	1036x315x230
Net Dimension (mm)	Outdoor (W*H*D)	685X430X260	780x540x250	780x540x250	820x600x345	845X695X335
	Indoor/Outdoor	7.0/22	8.5/28	10.0/34	13/47	13.5/55
Net Weight (kg)	Indoor (W*H*D)	755X324X260	865x350x265	1015x350x265	1135x435x315	1135x435x315
	Outdoor (W*H*D)	795X495X345	910x585x335	910x585x335	940x645x415	965X755X395
Gross Weight (kg)	Indoor/Outdoor	8.5/25	11.0/31	12.0/36	20.0/50.5	16.5/58
	Liquid	Ø6.35(1/4")	Ø6.35(1/4")	Ø6.35(1/4")	Ø9.53(3/8")	Ø9.53(3/8")
Piping Size (mm(inch))	Gas	Ø9.53(3/8")	Ø12.7(1/2")	Ø12.7(1/2")	Ø16.0(5/8")	Ø16.0(5/8")
	Refrigerant	R22	R22	R22	R22	R22

Remark:
 1.The above design and specifications are subject to change without prior notice.
 2.The noise level data reflects the level in anechoic chamber .

Dealer Details:

