

Four-way Cassette (Compact)



Four-way Cassette (Compact)

Features

- Auto Defrosting
- Auto Restart Function
- Anti-Cold Air Function
- Sleep Mode
- Built-in Drain Pump
- Independent Dehumidification
- Fresh Air

Specification_ Four-way Cassette(compact)

Indoor Unit		MCA2-12HR-Q	MCA2-18HR-Q
Outdoor Unit		MOUB-12H	MOU-18H-Q
Cooling Capacity	Btu/h	12000	18000
	kW	3.5	5.3
Heating Capacity	Btu/h	12000	19500
	kW	3.5	5.7
Power Supply	V~, Hz, Ph	220-240, 50, 1	220-240, 50, 1
Power Input (kW)	Cooling	1290	2060
	Heating	1130	1765
EER	W/W	2.73	2.56
COP	W/W	3.1	3.24
Air Flow Volume	m ³ /h	650/560/450	810/720/580
Noise Level (dB(A))	Hi/Med/Low	42/38/33	48/44/38
	Body (W×H×D)	570×260×570	570×260×570
	Panel (W×H×D)	647×506×647	647×506×647
Net Weight (kg)	Body	16	19
	Panel	2.5	2.5
	Body (W×H×D)	655×290×655	655×290×655
Packing Dimension (mm)	Panel (W×H×D)	715×123×715	715×123×715
	Body	19	21
	Panel	4.5	4.5
Gross Weight (kg)	Liquid	Φ6.35(1/4")	Φ6.35(1/4")
	Gas	Φ12.7(1/2")	Φ12.7(1/2")
	Drainage	ØØ25	ØØ25
Applicable Area	m ²	17~32	17~32
Refrigerant	-	R22	R22

1.The above design and specifications are subject to change of product improvement without prior notice.
2.The noise level data reflects the level in anechoic chamber.

Remark:
1.The above design and specifications are subject to change without prior notice.
2.The noise level data reflects the level in anechoic chamber.

Dealer Details: