

## GA Floor-Standing

# GA Floor-Standing



### Features



### Specification\_GA Floor-standing\_Series

Model		MFGA-48HR	MFGA-60HR
Cooling Capacity	Btu/h	48000	60000
	kW	14.1	17.6
Heating Capacity	Btu/h	48000+12000	60000
	kW	14.1+3.5	17.6
Power Supply	V~, Hz, Ph	380-415, 50, 3	380, 50, 3
Power Input (kW)	Cooling	5875	7175
	Heating	5000+3500	5460
Operating Current (A)	Cooling	10.1	12.4
	Heating	9.0+5.3	10.3
Starting Current	A	55	69
EER	W/W	2.41	2.45
COP	W/W	2.81	3.22
Air Flow Volume (m3/h)	Indoor	1750/1450	2320/2150/1270
Noise Level ( dB(A))	Indoor(Hi/Med/Lo)	56/51	48/54
	Outdoor	66	62
Net Dimension (mm)	Indoor (W*H*D)	550x1800x350	610x390x1925
	Outdoor (W*H*D)	990x965x345	900x350x1170
Net Weight (kg)	Indoor/Outdoor	52/82	59/104
Packing Dimension (mm)	Indoor (W*H*D)	1910x685x540	2040x745x545
	Outdoor (W*H*D)	1120x1100x435	1032x443x1307
Gross Weight (kg)	Indoor/Outdoor	70/93	80/108.5
Piping Size (mm(inch))	Liquid	Φ12.7(1/2")	Φ12.7(1/2")
	Gas	Φ19(3/4")	Φ19(3/4")
Refrigerant		R22	R22

Remark:  
1.The above design and specifications are subject to change without prior notice.  
2.The noise level data reflects the level in anechoic chamber .

### Dealer Details:

### Super Slim Design

With super slim indoor unit, the fashionable design brings great visual enjoyment as the home decoration.

